



FINISHES

EXTERNAL COLOR



INTERNAL COLOR



PROFILE LENGTHS mm.

843 | 1124 | 1405 | 1686 | 1967 | 2248

LIGHTING OPTIONS

DIFFUSERS

TRANSPARENT

POWER

STANDARD | HIGH

CRI

90

COLOR TEMPERATURE

2700K | 3000K | 4000K | TW

DIMMABLE OPTIONS

DALI | 1.10 | PUSH

LIGHT DISTRIBUTION

ASYMETRIC DOWN


LUMINAIRE INCLUDES

.PN


2 x Suspension cables 3m (each 2m)
NON-DIM DOWN: 1 x Feed Hose 3 x 0,75mm²
DIM DOWN: 1 x Feed Hose 5 x 0,75mm²

.SR

Surface mounting kit



Optimal distance from the wall: 0.5m.
Distancia óptima con respecto a la pared: 0.5m.



ON DEMAND

Emergency Lighting*
Special Color Temperature
RGB
Thematic LED
Wireless Control Options (Casambi)
CRI 80

* Delivered separately
(not installed in luminaire).

INSTALLATIONS



ALBA ASIMETRIC

REF 210009.PN | 210009.SR

.PN
PENDANT

·210009 ALBA ASIMETRIC
| PN - Pag. 242

.WS
WALL SURFACE

·210009 ALBA ASIMETRIC
| WS - Pag. 794

.SR
SURFACE


·210009 ALBA ASIMETRIC
| SR - Pag. 242

.RF
RECESSED FRAME

·210009 ALBA ASIMETRIC
| RF - Pag. 448

.TR
TRIMLESS

·210009 ALBA ASIMETRIC
| TR - Pag. 648



REF.	PROFILE LENGTH		FINISH	DIFFUSER	POWER	CRI	DOWNLIGHT *4 LUMEN				WATT		UPLIGHT .UP *2 LUMEN			WATT		DIMM
	MM	MM					.27	.30	.40	.TW *1	K	TW	.27	.30	.40	K	K	
210009	.03	843	●	.TP	.ST	.9	2295	2385	2475	5700-5910	18	38	265	274	349	4	.DA .PU .D1	
	.04	1124					3060	3180	3300	7600-7880	24	51	397	411	522	6		
	.05	1405					3825	3975	4125	9500-9850	30	64	529	548	696	8		
	.06	1686					4590	4770	4950	11400-11820	35	76	661	685	870	10		
	.07	1967					5355	5565	5775	13300-13790	41	89	793	822	1044	12		
	.08	2248					6120	6360	6600	15200-15760	47	102	925	958	1218	14		

REF.	PROFILE LENGTH		FINISH	DIFFUSER	POWER	CRI	DOWNLIGHT *4 LUMEN				WATT		UPLIGHT ▲.UP *2 LUMEN			WATT		DIMM
	MM	MM					.27	.30	.40			.27	.30	.40	K	K		
210009	.03	843	●	.TP	.HI	.9	4590	4767	4956	35	568	587	747	8	.DA .PU .D1			
	.04	1124					6120	6356	6608	47	851	880	1119	13				
	.05	1405					7650	7945	8260	59	1134	1173	1492	17				
	.06	1686					9180	9534	9912	71	1417	1466	1864	21				
	.07	1967					10710	11123	11564	83	1701	1760	2237	25				
	.08	2248					12240	12712	13216	94	1984	2053	2610	30				

Reference order **210009.XX** | **.SR** | **.PN** | **.XX.XX.XX9.XX.XX**

Total length = Profile length + 20mm + 2x3mm (Cover kit)

● Select finish



COMPONENTS

COVER KIT	REF.	FINISH
	TF06	●
	2x3mm.	

Reference order **TF06** | **.SR** | **.PN** | **.XX**

JOINTS

LINEAR JOINT
UR06

OPTIONS (.PN)

SUSPENSION KIT	REF.	DIMENSION	FINISH
	SC05	5M.	.SA
	SC07	7M.	
	SC10	10M.	

Reference order **SCXX.SA**

SUSPENSION ROD	REF.	DIMENSIONS	mm	FINISH
	SC21	.60	600	●
		.80	800	
		.100	1000	

Reference order **SC21.XX.XX**

Not-included, please select:

CONNECTION BOX	FINISH
	●
CB09.12	

Reference order **CB09.12.XX**



ALBA ASIMETRIC

REF 210009.PN | 210009.SR

PHOTOMETRY




TRANSPARENT PC

INCLUDED (.PN)



SC03.SA
WIRE 3M.

PROFILE



*1 Tunable White (TW) values correspond to 2700K and 6500K - TW is only available for DALI DT8 dimmable (.DA), CRI 80 (.8) 700mA. Los valores del blanco dinámico (TW) corresponden a 2700K y 6500K. -TW solo está disponible con protocolo DALI DT8 (.DA), CRI 80 (.8) 700mA.
*2 Down light (direct light) works at 500mA. La luz directa trabaja a 500mA.

new



FINISHES

● EXTERNAL COLOR



INTERNAL COLOR



● PROFILE LENGTHS mm.

843 | 1124 | 1405 | 1686 | 1967 | 2248

LIGHTING OPTIONS

■ DIFFUSERS

TRANSPARENT

POWER

STANDARD | HIGH

CRI

90

COLOR TEMPERATURE

2700K | 3000K | 4000K | TW

▼ DIMMABLE OPTIONS



DALI | 1.10 | PUSH

▲ LIGHT DISTRIBUTION

ASYMETRIC DOWN

LUMINAIRE INCLUDES

Recessed with frame mounting kit



ON DEMAND

- Emergency Lighting*
- Well-Certified LED Boards
- Special Color Temperature
- RGB
- Thematic LED
- Wireless Control Options (Casambi)
- CRI 80

* Delivered separately (not installed in luminaire).

INSTALLATIONS



ALBA ASIMETRIC

REF 210009.RF



.PN
PENDANT

·210009 ALBA ASIMETRIC
| PN - Pag. 242



.WS
WALL SURFACE

·210009 ALBA ASIMETRIC
| WS - Pag. 794



.SR
SURFACE

·210009 ALBA ASIMETRIC
| SR - Pag. 242




.RF
RECESSED FRAME

·210009 ALBA ASIMETRIC
| RF - Pag. 448



.TR
TRIMLESS

·210009 ALBA ASIMETRIC
| TR - Pag. 648






RECESSED FRAME

REF.	PROFILE LENGTH		FINISH	DIFFUSER	POWER	CRI	DOWNLIGHT LUMEN				WATT		DIMM
	MM	MM					.27	.30	.40	.TW*2	K	TW	
210009	.03	843	●	.TP	.ST	.9	2295	2385	2475	5700-5910	18	38	.DA .PU .D1
	.04	1124					3060	3180	3300	7600-7880	24	51	
	.05	1405					3825	3975	4125	9500-9850	30	64	
	.06	1686					4590	4770	4950	11400-11820	35	76	
	.07	1967					5355	5565	5775	13300-13790	41	89	
	.08	2248					6120	6360	6600	15200-15760	47	102	

REF.	PROFILE LENGTH		FINISH	DIFFUSER	POWER	CRI	DOWNLIGHT LUMEN			WATT	DIMM
	MM	MM					.27	.30	.40		
210009	.03	843	●	.TP	.HI	.9	4590	4767	4956	35	.DA .PU .D1
	.04	1124					6120	6356	6608	47	
	.05	1405					7650	7945	8260	59	
	.06	1686					9180	9534	9912	71	
	.07	1967					10710	11123	11564	83	
	.08	2248					12240	12712	13216	94	


Reference order | 210009.XX.RF.XX.XX.XX.XX.XX.XX.XX

 Total length = Profile length + 10mm + 2x8mm (Cover kit)
 (Total length - 8mm) x 51mm
 100mm

● Select finish



COMPONENTS

COVER KIT	REF.	FINISH
	TF06 2x8mm.	●

Reference order | TF06.RF.XX

JOINTS



.RF
RECESSED FRAME



ALBA ASIMETRIC

REF 210009.RF

PHOTOMETRY




TRANSPARENT PC

INCLUDED



RF INSTALLATION KIT

PROFILE



*1 Tunable White (TW) values correspond to 2700K and 6500K - TW is only available for DALI DT8 dimmable (.DA), CRI 80 (8) 700mA. Los valores del blanco dinámico (TW) corresponden a 2700K y 6500K. - TW solo está disponible con protocolo DALI DT8 (.DA), CRI 80 (8) 700mA.
 *2 Down light (direct light) works at 500mA. La luz directa trabaja a 500mA.

new



FINISHES

● EXTERNAL COLOR



INTERNAL COLOR



● PROFILE LENGTHS mm.

843 | 1124 | 1405 | 1686 | 1967 | 2248

LIGHTING OPTIONS

■ DIFFUSERS

TRANSPARENT

POWER

STANDARD | HIGH

CRI

90

COLOR TEMPERATURE

2700K | 3000K | 4000K | TW

▼ DIMMABLE OPTIONS



DALI | 1.10 | PUSH

▲ LIGHT DISTRIBUTION

ASYMETRIC DOWN

LUMINAIRE INCLUDES

Trimless mounting kit



ON DEMAND

Emergency Lighting*
Special Color Temperature
RGB
Thematic LED
Wireless Control Options (Casambi)
CRI 80

* Delivered separately
(not installed in luminaire).

INSTALLATIONS

.PN
PENDANT

·210009 ALBA ASIMETRIC
| PN - Pag. 242

.WS
WALL SURFACE

·210009 ALBA ASIMETRIC
| WS - Pag. 794

.SR
SURFACE

·210009 ALBA ASIMETRIC
| SR - Pag. 242

.RF
RECESSED FRAME

·210009 ALBA ASIMETRIC
| RF - Pag. 448


.TR
TRIMLESS

·210009 ALBA ASIMETRIC
| TR - Pag. 648



ALBA ASIMETRIC

REF 210009.TR






TRIMLESS

REF.	PROFILE LENGTH		FINISH	DIFFUSER	POWER	CRI	DOWNLIGHT LUMEN				WATT		DIMM
	MM	MM					.27	.30	.40	.TW*2	K	TW	
210009	.03	843	●	.TP	.ST	.9	2295	2385	2475	5700-5910	18	38	.DA .PU .D1
	.04	1124					3060	3180	3300	7600-7880	24	51	
	.05	1405					3825	3975	4125	9500-9850	30	64	
	.06	1686					4590	4770	4950	11400-11820	35	76	
	.07	1967					5355	5565	5775	13300-13790	41	89	
	.08	2248					6120	6360	6600	15200-15760	47	102	

REF.	PROFILE LENGTH		FINISH	DIFFUSER	POWER	CRI	DOWNLIGHT LUMEN			WATT	DIMM
	MM	MM					.27	.30	.40		
210009	.03	843	●	.TP	.HI	.9	4590	4767	4956	35	.DA .PU .D1
	.04	1124					6120	6356	6608	47	
	.05	1405					7650	7945	8260	59	
	.06	1686					9180	9534	9912	71	
	.07	1967					10710	11123	11564	83	
	.08	2248					12240	12712	13216	94	


Reference order | 210009.XX.TR.XX.XX.XX.XX.XX.XX.XX

 Total length = Profile length + 10mm + 2x2mm (Cover kit)
 (Total length + 2mm) x 65mm
 100mm

● Select finish



COMPONENTS

COVER KIT	REF.	FINISH
	TF06	●
	2x2mm.	

Reference order | TF06.TR.XX

JOINTS



ALBA ASIMETRIC

REF 210009.TR


PHOTOMETRY



TRANSPARENT PC

PROFILE

12,5mm Standard Ceiling



*Tunable White (TW) values correspond to 2700K and 6500K - TW is only available for DALI DT8 dimmable (.DA), CRI 80 (.8) 700mA. Los valores del blanco dinámico (TW) corresponden a 2700K y 6500K. -TW solo está disponible con protocolo DALI DT8 (.DA), CRI 80 (.8) 700mA.
 *2 Down light (direct light) works at 500mA. La luz directa trabaja a 500mA.



FINISHES

EXTERNAL COLOR



INTERNAL COLOR



LENGTHS mm.

307 | 447 | 588

LIGHTING OPTIONS

DIFFUSERS

TRANSPARENT

POWER

STANDARD | HIGH

CRI

90

COLOR TEMPERATURE

2700K | 3000K | 4000K | TW

DIMMABLE OPTIONS

DALI | 1.10 | PUSH

LIGHT DISTRIBUTION

ASYMETRIC DOWN

LUMINAIRE INCLUDES

Wall surface mounting kit
Cover Kit



ON DEMAND

Emergency Lighting*
Special Color Temperature
RGB
Thematic LED
Wireless Control Options (Casambi)
CRI 80

* Delivered separately
(not installed in luminaire).

.WS

WALL SURFACE

INSTALLATIONS



ALBA ASIMETRIC

REF 210009.WS

.PN
PENDANT

·210009 ALBA ASIMETRIC
| PN - Pag. 242

.WS
WALL SURFACE

·210009 ALBA ASIMETRIC
| WS - Pag. 794

.SR
SURFACE


·210009 ALBA ASIMETRIC
| SR - Pag. 242

.RF
RECESSED FRAME

·210009 ALBA ASIMETRIC
| RF - Pag. 448

.TR
TRIMLESS


·210009 ALBA ASIMETRIC
| TR - Pag. 648



REF.	DIMENSION		FINISH	DIFFUSER	POWER	CRI	DOWNLIGHT LUMEN				WATT		DIMM
	MM	MM					.27	.30	.40	.TW*2	K	TW	
210009	.01	307	●	.TP	.ST	.9	765	795	825	1900-1970	6	13	.DA .PU .D1
	.02	447					1148	1193	1238	2850-2955	9	20	
	.03	588					1530	1590	1650	3800-3940	12	26	


REF.	DIMENSION		FINISH	DIFFUSER	POWER	CRI	DOWNLIGHT LUMEN			WATT		DIMM
	MM	MM					.27	.30	.40	K	TW	
210009	.01	307	●	.TP	.HI	.9	1530	1589	1652	12		.DA .PU .D1
	.02	447					2295	2384	2478	18		
	.03	588					3060	3178	3304	24		

Reference order | 210009.XX.WS.XX.XX.XX.9.XX.XX



WALL SURFACE

Select finish



ALBA ASIMETRIC

REF 210009.WS

PHOTOMETRY




TRANSPARENT PC

INCLUDED




COVER KIT



WALL SURFACE MOUNTING KIT

PROFILE



*Tunable White (TW) values correspond to 2700K and 6500K - TW is only available for DALI DT8 dimmable (.DA), CRI 80 (8) 700mA. Los valores del blanco dinámico (TW) corresponden a 2700K y 6500K. -TW solo está disponible con protocolo DALI DT8 (.DA), CRI 80 (8) 700mA.
 *2 Down light (direct light) works at 500mA. La luz directa trabaja a 500mA.